

A36 Hinges & pivots
B Pulls & plates
C Flush bolts & coordinators
D Latches, catches & bolts
E Stops
F Exterior hardware
G Miscellaneous hardware



224HD Full mortise - door edge protector

- For 1 3/4" doors
- Door edge protector
- Spread bearing design
- Non handed for custom cut lengths
- 1/16" Door Inset
- 48" Maximum door width
- Beveled or square edge doors
- For doors weighing up to 450 pounds without reinforcing, 600 pounds with reinforcing

Certifications

- Meets ANSI 156.26 for 150lbs
- UL10C certified

Standard lengths

- 83", 85", 95", 120"

Standard mounting hardware

- 12-24 x 3/4" Steel self drilling / self tapping phillips head screw

Finishes

- Clear Anodized (US28), Dark Bronze Anodized (313AN)

Custom anodizing and painting are available, consult factory.

Options:


- EPTElectric power transfer

Optional mounting hardware:

- SECHM.....Security screws - hollow metal door and frame
- SECWDHM.....Security screws - 1/2 wood, 1/2 hollow metal
- SECWDWD.....Security screws - wood door and frame
- TF.....Thread forming screws
- TEKWD.....1/2 self drill, self tap 1/2 wood
- WD.....Wood door and frame

For single door applications:

For pairs of doors see chart and general information



5/16" Clearance for Square Edge Door
11/32" Clearance for Beveled Edge Door