Floor stops IVES



FS18S Floor stop - 11/2" FS18L Floor stop - 31/2"

- Security door stops designed for use in high vandalism areas
- Molded from black flame resistant, resilient material around a heavy-duty stud
- Once grouted in concrete, leaves no exposed fasteners to be tampered with or removed
- Ideal for jail or security cell areas where floor mounted stops are required
- FS18L also ideal for concrete wall applications

Material substrate

Made from rubber

Finishes

Black rubber

Dimensions

Dimensions

Dimensions

Overall height: 1-5/16"Base diameter: 1-1/4"

Overall height: 2-5/8"Base size: 1-1/2" W x 2-3/4" L

- FS18S Height: 1-1/2"
- FS18S Diameter: 2"
- FS18S Stud length: 2-1/2"
- FS18L Height: 3-1/2"
- FS18L Diameter: 2"
- FS18L Stud length: 2-1/2"

FS434 Floor stop

- For undercut doors up to 1-1/2"
- Packed with fasteners for light duty masonry and wood applications
- Soft, resilient black rubber

Material substrate

• Made from wrought steel

Available accessory items

• Replaceable soft, resilient black rubber.

Finishes

ВНМА	Description	Substrate	Finish
604	Zinc Plated	Steel	US2C



430 Floor door stop

- For undercut doors up to 1-1/2".
- · Welded wood screws for wood applications.
- White rubber tip

Material substrate

Made from cast brass and aluminum

Available accessory items

- Replaceable white tips
- Black rubber tips

Finishes - Brass

BHMA	Description	Substrate	Finish		
605	Bright brass	Brass	US3		
606	Satin brass	Brass	US4		
609	Blackened brass	Brass	US5		
613	Oil rubbed bronze	Brass	US10B		
619	Satin nickel	Brass	US15		
625	Bright chrome	Brass	US26		
626	Satin chrome	Brass	US26D		

Finishes - Aluminum

Thistes / torring in						
BHMA	Description	Substrate	Finish			
666	Bright brass	Aluminum	АЗ			
	Blackened brass	Aluminum	A5			
669	Bright nickel	Aluminum	A14			
673	Aluminum clear coat	Aluminum	A92			

For other colors, consult factory.