V12



HURRICANE & HIGH WIND VELOCITY PAK: VLFEZHRC PAK™

Beveled Vision Lite With Continuous Glass Retainer. Recommended for Applications Requiring Safety From Wind-Borne Debris. Includes Tested and Approved Polycarbonate Glazing and Caulking.

Now Miami Dade, County Florida and Florida Building Code Approved!

SPECIFICATIONS:

Material:	20 gauge galvanneal steel frame. Min size 3" x 3", max 23 5/8" x 61 3/8". See Windstorm Rating Below			
Construction:	1-1/4" trim with mitered and welded corners, beveled return, and countersunk mounting holes in the bevel. Screws fasten from room side into pre-punched mounting holes. This mounting method leaves corridor side of frame free of fasteners for aesthetic and security purposes.			
Powder Coat Finishes:	(B) Mineral Bronze (standard color) (BK) Black (FBK) Flat Black (W) White (SB) SC Beige (SI) Silver (BRA) Brass (S) Sand (AB) AMS Beige (G) Gray View Colors Online			
Door:	For 1-3/4" door. Door cutout = order size.			
Fasteners:	#8 x 1" flathead phillips head screws to match finish.			
Glazing:	1/4" Lexan ® Glazing Included Glass size is 1" under order size Occanning Glazing Included Occanning Glazing Occanning Glazi			
Caulking:	D 0 : 0050 (III			
	Dow Corning 995® for caulking on both sides of glazing. Glazing & Caulking included with Vision Frame			
Caulking: Dow Corning 995® for caulking on both sides of glazing. Glazing & Caulking included with Vision Frame Severe Windstorm Approved Vision Frame Tested in Accordance with W/N 14475 ASTM E283, ASTM E331, A870, AAMA 1304 Cyclic wind Pressure Loading: FBC & TAS 203-94 Large Missile Impact Test: FBC & TAS 201-94. Air Infiltration Test, Uniform Static Air Pressure Test-Loading, Water Resistance Test, Forced Entry Test: FBC 2411, 3.2.1 & TAS 202-94 Impact (ft lb) 350 Missile Level D, DP Rating (PSF) 55 Florida Building Code Approval File # FL13187-R3 New Miami Dade, County NOA: 18-1220-12 Expires 7/03/2020				
Fasteners:	Torx Other:			
Order Format: VLFEZHRC Example: VLFEZHRC 1212B PAK W H Color				

Interpretation of Fire and Building Codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

AIR	Distributor:	Width:	_x Height:	
	Architect:	Quantity:		
ACTIVAR _{INC.}	Contractor:	Model:		
© 2019 Activar Construction Products Group, Inc.	Project:	Date:	Version: ALPDS1901	
800-554-6077 Quot	ES@ACTIVARCPG.COM ORDERS@ACTIVARCPG.COI	M SALES@ACT	IVARCPG.COM	
VISIT <u>www.activarcpg.com</u> for the most updated product information before ordering				
MFG: COMMERCE CA, BLOOMINGTON, MN • WAREHOUSES: LANCASTER PA, ATLANTA GA, CHICAGO IL, SEATTLE WA, FORT MYERS FL, DALLAS TX, FARGO ND, OMAHA NE				