



strike





Universal strike

054 Dutch door bolt

- Practical, rugged, attractive bolt for application on dutch doors as well as other areas
- Chamfered rod end draws the two leaves of door tightly together
- Sufficient tolerance provided in strike opening to allow for misalignment of door leaves and also prevents binding of bolt
- Decorative 1" diameter knob designed to facilitate bolt operation
- Units packed with wood screws
- Packed with Standard Strike (SS), Mortise Strike (MS) and Universal Strike (US)

Certifications

Meets ANSI/BHMA A156.16

Material substrate

Made from solid brass

Dimensions

- Throw: 5/8"
- Projection: 1-1/8"
- Half round rod: 5/8"
- Overall width: 1-5/8"
- Rod length: 4-1/4"
- Overall length: specify 4-3/8" (including knob)

Finishes

ВНМА	Description	Substrate	Finish
605	Bright brass	Brass	B3
606	Satin brass	Brass	B4
612	Satin bronze	Brass	B10
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D

For other colors, consult factory.

S48 Mortise door bolt

- Brass oval turn knob and escutcheon
- Steel bolt for extra strength
- Rack is milled for precision fit with pinion
- Units packed with wood screws

Certifications

Meets ANSI/BHMA A156.16

Material substrate

Made from brass and steel

Dimensions

- Backset: 1-3/4"
- Bolt throw: 1/2"
- Bolt diameter: 1/2"
- Case: 2-1/2" long x 9/16" diameter
- Strike: 1-3/4" high x 7/8" wide

Finishes

ВНМА	Description	Substrate	Finish
605	Bright brass	Brass	B3
609	Blackened brass	Brass	B5
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D

For other colors, consult factory,